

METHOD FOR DETECTING MOTION PIXELS IN IMAGE

BACKGROUND OF THE INVENTION

1. Field of the invention

This invention relates to a method for detecting motion pixels in image, in particular, used in digit monitoring systems, image processing systems and graphics identification system.

2. Description of the prior art

A conventional method for detecting motion pixels in image is performed by subtracting background image from current image so as to obtain the difference image. Then, in the difference image, the pixel values whose absolute values are greater than preset threshold are used as a binarization threshold indicating motion pixels. On the other hand, the image difference resulted from illumination change is likely to be regarded as presence of motion pixels due to erroneous judgment.

Accordingly, the above-described prior art method is not a perfect design and has still many disadvantages to be solved. In views of the above-described disadvantages resulted from the conventional method, the applicant keeps on carving unflaggingly to develop a method for detecting motion pixels in image according to the present invention through wholehearted experience and research.

SUMMARY OF THE INVENTION

An object of the invention is to provide a method for detecting motion pixels in image, which is capable of automatically adjusting and judging whether

the binarization threshold indicating motion pixels is present, depending on image complexity.

Another object of the invention is to provide a method for detecting motion pixels in image in order to prevent erroneous judgment of motion pixels in difference image due to illumination change.

The present invention relates to a method for detecting motion pixels in image by counting the occurrences of all absolute pixel values in the difference image between current image and background image or the updated difference image to plot a cumulative histogram, and finding a threshold for binarizing the pixel values from the cumulative histogram. Since the points in the cumulative histogram is in ascending order without irregular fluctuation of the typical bar chart, the threshold for binarizing the pixel values can be determined more easily. The present invention utilizes the approximation method to plot the cumulative histogram, wherein the turning point in ascending order or the point ascending the slowest is used as the binarization threshold. Since the difference image between current image and background image or the updated difference image is used to obtain a better binarized result, the motion pixels in the image can be detected more accurately than in the prior art. Furthermore, the present invention uses all or part of the pixel values, in the difference image, whose absolute values are smaller than or equal to the binarization threshold to compensate the effect of illumination change and to obtain the updated difference image. The effect of illumination change on the updated difference image is obviated accordingly.

These features and advantages of the present invention will be fully understood and appreciated from the following detailed description of the accompanying Drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings disclose an illustrative embodiment of the present invention which serves to exemplify the various advantages and objects hereof, and are as follows:

5 Fig. 1 is a flowchart of an embodiment according to the present invention;

 Fig. 2 is a flowchart illustrating an embodiment of finding a binarization threshold from the difference image or the updated difference image according to the present invention; and

 Fig. 3 is a schematic diagram of an embodiment of finding a binarization
10 threshold from the cumulative histogram of absolute pixels.

 These features and advantages of the present invention will be fully understood and appreciated from the following detailed description of the accompanying Drawings.

DETAILED DESCRIPTION OF THE PREFERRED 15 EMBODIMENT

 Referring to Fig.1, a method for detecting motion pixels in image comprises the following steps:

 Step 1: obtaining difference image between current image and background image, wherein the counting way can be performed by subtracting the background
20 image from the current image, eliminating the background image from the current image or subtracting the background image after performing a logarithmic operation from the current image after performing a logarithmic operation;

 Step 2: finding a binarization threshold from the distribution of all absolute pixel values in the difference image, wherein an embodiment of finding a

binarization threshold from the difference image or the updated difference image and illustrated with reference to the flowchart of Fig. 2 comprises the following sub-steps:

- 5 2-1: counting the occurrences of all absolute pixel values to plot the cumulative histogram, wherein the transverse axis of the cumulative histogram indicates all possible absolute pixel values arranged in ascending order, and the longitudinal axis indicates the cumulative occurrence count equal to or smaller than the absolute pixel values;
- 10 2-2: finding a value between the minimum absolute pixel value and the maximum absolute pixel value, such that the two linear segments constructed by the occurrence count of the minimum absolute pixel value, the cumulative occurrence count of the absolute pixel values equal to or smaller than the selected value and the cumulative occurrence count of the absolute pixel values
- 15 equal to or smaller than the maximum absolute pixel value optimally approximate the cumulative histogram; and defining this value as the binarization threshold; Referring to Fig. 3, an embodiment of finding a binarization threshold from cumulative
- 20 histogram of absolute pixels is illustrated. Provided that the coordinate of every point in the linear segments constructed by the minimum absolute pixel value, the selected value and the maximum absolute pixel value is defined as (i, L_i) , and the coordinate of every point in the envelope line of the cumulative
- 25 histogram is defined as (i, E_i) , the pixel value obtaining the minimum of $\sum_i |L_i - E_i|$ is the binarization threshold. Alternatively, the pixel value obtaining the minimum of

$\sum_i (L_i - E_i)^2$ is also regarded as the binarization threshold.

Alternatively, the pixel value obtaining the maximum correlation coefficient of $\{L_i\}$ and $\{E_i\}$ sequences can also be regarded as the binarization threshold.

5 Step 3: using all or part of the pixel values, in the difference image, whose absolute values are smaller than or equal to binarization threshold to compensate the effect of illumination change and to obtain the updated difference image; in the compensating method, an average value of all or part of the pixel values, in difference image, whose absolute values are smaller than or equal to binarization
10 threshold is used as a correction value, and then the updated difference image is obtained by subtracting this correction value from difference image or eliminating this correction value from difference image.

 Step 4: finding a binarization threshold from the distribution of all absolute pixel values in updated difference image, changing the pixel values whose
15 absolute values are larger than the binarization threshold to high, and changing the pixel values whose absolute values are equal to or smaller than the binarization threshold to low such that the binarized updated difference image is obtained through these steps, wherein an embodiment of finding a binarization threshold from the difference image or the updated difference image and illustrated with
20 reference to the flowchart of Fig. 2 comprises the following sub-steps:

 4-1: Counting the occurrences of all absolute pixel values to plot the cumulative histogram, wherein the transverse axis of the cumulative histogram indicates all possible absolute pixel values arranged in ascending order, and the longitudinal axis indicates
25 the cumulative occurrence count of the absolute pixel values;

 4-2: Finding a value between the minimum absolute pixel value and the maximum absolute pixel value, such that the two linear

segments constructed by the occurrence count of the minimum
 absolute pixel value, the cumulative occurrence count of the
 absolute pixel values equal to or smaller than the selected value
 and the cumulative occurrence count of the absolute pixel values
 equal to or smaller than the maximum absolute pixel value
 optimally approximate the cumulative histogram; and defining
 this value as the binarization threshold; Referring to Fig. 3, an
 embodiment of finding a binarization threshold from cumulative
 histogram of absolute pixels is illustrated. Provided that the
 coordinate of every point in the linear segments constructed by
 the minimum absolute pixel value, the selected value and the
 maximum absolute pixel value is defined as (i, L_i) , and the
 coordinate of every point in the envelope line of the cumulative
 histogram is defined as (i, E_i) , the pixel value obtaining the
 minimum of $\sum_i |L_i - E_i|$ is the binarization threshold.
 Alternatively, the pixel value obtaining the minimum of
 $\sum_i (L_i - E_i)^2$ is also regarded as the binarization threshold.
 Alternatively, the pixel value obtaining the maximum correlation
 coefficient of $\{L_i\}$ and $\{E_i\}$ sequences can also be regarded as the
 binarization threshold.

Step 5: The pixels in the binarized updated difference image whose values
 are high are determined as the motion pixels.

The method for detecting motion pixels in image provided by the present
 invention, when comparing with other previous conventional technologies, has
 following advantages:

1. The present invention utilizes the approximation method to plot the
 cumulative histogram, wherein the turning point in ascending order or the point

ascending the slowest is used as the binarization threshold. Since the difference image between current image and background image or the updated difference image is used to obtain a better binarized result, the motion pixels in the image can be detected more accurately than in the prior art.

- 5 2. The present invention uses all or part of the pixel values, in difference image, whose absolute values are smaller than or equal to binarization threshold to compensate the effect of illumination change and to obtain the updated difference image. The effect of illumination change on the updated difference image is obviated accordingly.

10 Many changes and modifications in the above described embodiment of the invention can, of course, be carried out without departing from the scope thereof. Accordingly, to promote the progress in science and the useful arts, the invention is disclosed and is intended to be limited only by the scope of the appended claims.